

CATENERA KSB 6, 8, 12

Adhesive dampening greases of medium to high shear viscosity



Your benefits at a glance

- More comfortable operation (haptics) of mechanical components as friction points are dampened by the lubricant
- Better component function e.g. due to good adhesion retaining the lubricant at the friction point
- CATENERA KSB 8 is certified according to NSF ISO 21469, supporting the compliance with the hygienic requirements in your production. You will find further information about ISO Standard 21469 on our website www.klueber.com

Your requirements - our solution

CATENERA KSB 6, 8, 12 are adhesive dampening greases based on synthetic hydrocarbon, ester and paraffin oil. They contain silicate as thickener.

In the food and pharmaceuticals industries, CATENERA KSB 8 may be preferably used for applications where technically unavoidable contact with the food product cannot be excluded.

CATENERA KSB 8 is NSF H1 registered and therefore complies with FDA 21 CFR § 178.3570. The lubricant was developed for incidental contact with products and packaging materials in the food-processing, cosmetics, pharmaceutical or animal feed industries. The use of CATENERA KSB 8 can contribute to increase reliability of your production processes. We nevertheless recommend conducting an additional risk analysis, e.g. HACCP.

Application

CATENERA KSB greases are used for friction points requiring high mechanical dampening and good adhesion, e.g. low-speed rolling and plain bearings, small gears, threaded spindles, eyepieces and binoculars.

CATENERA KSB is available in three shear viscosity grades in order to meet dampening and adhesion requirements.

For even higher shear viscosities we refer to the Klübersynth RA greases.

Application notes

CATENERA KSB greases can be applied by brush, spatula, grease gun, automatic metering systems for small quantities, grease cartridge and the usual metering systems. Owing to the many different elastomer and plastic compositions their compatibility has to be checked prior to series application.

Variations in the colour of products manufactured by means of chemical processes are a common phenomenon. Possible causes are, for example, variations in the colour of natural raw materials. All these colour variations, however, are in no way an indication of a change in the quality of the product.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	CATENERA KSB 6	CATENERA KSB 8	CATENERA KSB 12
Cartridge 400 g		+	
Can 1 kg	+	+	+
Bucket 25 kg	+	+	+

CATENERA KSB 6, 8, 12

Adhesive dampening greases of medium to high shear viscosity



Characteristics	CATENERA KSB 6	CATENERA KSB 8	CATENERA KSB 12
Article number	007002	007003	007004
Composition, thickener	silicate	silicate	silicate
Composition, type of oil	ester oil , paraffinic mineral oil , synthetic hydrocarbon oil	ester oil , paraffinic mineral oil , synthetic hydrocarbon oil	ester oil , paraffinic mineral oil , synthetic hydrocarbon oil
Appearance	almost transparent	almost transparent	almost transparent
Colour space	brown	beige	beige
Texture	homogeneous , long fibrous	fibrous , homogeneous	fibrous , homogeneous
Service temperature, lower limit	-35 °C	-30 °C	-30 °C
Service temperature, upper limit	120 °C	120 °C	120 °C
NSF H1 registration number		113755	
Density, Klüber method: PN 024, 20°C	approx. 0.93 g/cm ³	approx. 0.93 g/cm ³	approx. 0.93 g/cm ³
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, lower limit	350 0.1 mm	260 0.1 mm	180 0.1 mm
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, upper limit	390 0.1 mm	300 0.1 mm	220 0.1 mm
Shear viscosity, Klüber method: PN 008@DIN 53019-1, equipment: rotational viscometer, 25°C, 300 s ⁻¹ , lower limit	4000 mPas	6000 mPas	8000 mPas
Shear viscosity, Klüber method: PN 008@DIN 53019-1, equipment: rotational viscometer, 25°C, 300 s ⁻¹ , upper limit	7000 mPas	10000 mPas	20000 mPas
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	18 months	12 months	18 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 90 years.

Klüber Lubrication München GmbH & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München GmbH & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München GmbH & Co. KG and if source is indicated and voucher copy is forwarded.