

# ISOFLEX TOPAS NB 5051

Synthetic long-term grease



## Your benefits at a glance

- Synthetic long-term lubricating grease for a wide service temperature range
- Low starting and running torque
- Good wear protection
- Good corrosion protection
- Resistant to oxidation and ageing

## Your requirements - our solution

ISOFLEX TOPAS NB 5051 is a beige-colored, homogeneous, short-fibred long-term grease for a wide service temperature range. It is a dynamically light grease consisting of synthetic hydrocarbon oil and barium complex soap. The barium complex soap used is not classified as harmful under the EU Directives on dangerous substances.

ISOFLEX TOPAS NB 5051 ensures low starting and running torques. In addition, it is resistant to oxidation and ageing, and protects reliably against corrosion.

## Application

ISOFLEX TOPAS NB 5051 is used for plain and rolling bearings (e.g. in automotive engineering) and for gas meters. It is also used in small gears, where it reduces the noise produced by the gear wheels. ISOFLEX TOPAS NB 5051 is also suitable for the lubrication of tooth

flanks in precision gears (e.g. bevel gears in milling machines, electromechanical actuators for valves).

Its good adhesion on smooth surfaces makes it ideal for the running-in lubrication (assembly) of plastic and composite bearings.

## Application notes

The lubricant is applied by brush or conventional metering systems. Gears are dip-feed lubricated. Owing to the different compositions of elastomers and plastic materials, compatibility tests are indispensable before series application.

## Material safety data sheets

Material safety data sheets can be requested via our website [www.klueber.com](http://www.klueber.com). You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	ISOFLEX TOPAS NB 5051
Cartridge 400 g	+
Can 500 g	+
Can 1 kg	+
Bucket 18 kg	+
Bucket 25 kg	+
Drum 180 kg	+

  

Characteristics	ISOFLEX TOPAS NB 5051
Article number	004128

# ISOFLEX TOPAS NB 5051

Synthetic long-term grease



Characteristics	ISOFLEX TOPAS NB 5051
Composition, thickener	barium complex soap
Composition, type of oil	synthetic hydrocarbon oil
Colour space	beige
Texture	homogeneous , short fibrous
Service temperature, lower limit	-60 °C
Service temperature, upper limit	130 °C
Density, Klüber method: PN 024, 20°C	approx. 0.91 g/cm <sup>3</sup>
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, lower limit	385 0.1 mm
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, upper limit	415 0.1 mm
Shear viscosity, Klüber method: PN 008@DIN 53019-1, equipment: rotational viscometer, 25°C, 300 s <sup>-1</sup> , lower limit	700 mPas
Shear viscosity, Klüber method: PN 008@DIN 53019-1, equipment: rotational viscometer, 25°C, 300 s <sup>-1</sup> , upper limit	1500 mPas
Kinematic viscosity of the base oil, DIN EN ISO 3104 / DIN 51562-1 / ASTM D445 / ASTM D7042, 100°C	approx. 5.9 mm <sup>2</sup> /s
Kinematic viscosity of the base oil, DIN EN ISO 3104 / DIN 51562-1 / ASTM D445 / ASTM D7042, 40°C	approx. 30 mm <sup>2</sup> /s
SKF-EMCOR, DIN 51802, Klüber method: distilled water, 168 h	≤ 1 corrosion degree
Flow pressure, DIN 51805-2, -60°C	≤ 1400 mbar
Dropping point, DIN ISO 2176 / IP 396	≥ 170 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

## Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 90 years.

Klüber Lubrication München GmbH & Co. KG /  
Geisenhausenerstraße 7 / 81379 München / Germany /  
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München GmbH & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München GmbH & Co. KG and if source is indicated and voucher copy is forwarded.