

Klüberlub BE 71-501

Special lubricating grease for rolling and plain bearings



Your benefits at a glance

- Versatile lubricant for highly loaded rolling and plain bearings
- Reduced operating and maintenance costs due to low consumption
- Good wear protection when exposed to high loads
- Long grease life due to low operating temperatures and friction
- Low waste water disposal costs and long service life of components due to good water resistance

Your requirements - our solution

Klüberlub BE 71-501 is a light-coloured lubricating grease which offers good compatibility with nonferrous metals like those used for example as plain bearing material. Due to its special formulation and solid lubricants, wear is low when exposed to rotating and oscillating motion and high impact loads. Klüberlub BE 71-501 is resistant to water and has a good sealing effect. The additives contained in this product enhance its ageing resistance.

Application

Klüberlub BE 71-501 can contribute to extending the service life of plain bearings where low-wear and low-friction operation is required under mixed friction conditions. This special grease meets the requirements in terms of reduced lubricant consumption and extended lubrication intervals in forging presses while maintaining a constant temperature level in the plain bearing. Klüberlub BE 71-501 can also be used for plain bearings subject to high loads in the plastics processing industry and building machines (e.g. ring-roll mills) and in construction machines. Owing to the good results

achieved on the rolling bearing test rigs and the good pumpability of the grease in commercial central lubrication systems. Klüberlub BE 71-501 is also suitable for high-temperature applications, especially in the steel industry (e.g. ring-roller mills) and wood-working industry (e.g. rolling bearings in pelleting presses).

Application notes

Klüberlub BE 71-501 can be applied by means of central lubrication systems or by brush, spatula, grease gun and automatic metering devices. When switching to Klüberlub BE 71-501, the lubricant consumption should be reduced step by step in order to ensure that used lubricant, wear particles and impurities are completely removed from the bearing.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	Klüberlub BE 71-501
Cartridge 400 g	+
Can 1 kg	+
Bucket 25 kg	+
Drum 180 kg	+

Characteristics	Klüberlub BE 71-501
Article number	020160

Klüberlub BE 71-501

Special lubricating grease for rolling and plain bearings



Characteristics	Klüberlub BE 71-501
Composition	solid lubricant
Composition, thickener	polyurea
Composition, type of oil	mineral oil
Colour space	yellow
Service temperature, lower limit	-20 °C
Service temperature, upper limit, in case of continuous lubrication	160 °C
Service temperature, DIN 51825, upper limit, rolling bearing	140 °C
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, lower limit	310 0.1 mm
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, upper limit	340 0.1 mm
Kinematic viscosity of the base oil, DIN EN ISO 3104 / DIN 51562-1 / ASTM D445 / ASTM D7042, 100°C	approx. 32 mm ² /s
Kinematic viscosity of the base oil, DIN EN ISO 3104 / DIN 51562-1 / ASTM D445 / ASTM D7042, 40°C	approx. 490 mm ² /s
Copper corrosion, DIN 51811, 24 h, 100°C	1 - 100 - 24 corrosion degree
SKF-EMCOR, DIN 51802, Klüber method: distilled water, 168 h	≤ 2 corrosion degree
Flow pressure, DIN 51805-2, -20°C	≤ 1400 mbar
Dropping point, DIN ISO 2176 / IP 396	≥ 200 °C
Four-ball tester: wear characteristics, DIN 51350-5, E: 1000 N, 1 min, wear scar diameter	≤ 1 mm
Four-ball tester, welding load, DIN 51350-4	≥ 4000 N
Speed factor (n x dm)	approx. 300000 mm/min
Water resistance, DIN 51807-1, 3 h, 90°C	≤ 1 - 90 rating
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	24 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 90 years.

Klüber Lubrication München GmbH & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München GmbH & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München GmbH & Co. KG and if source is indicated and voucher copy is forwarded.