

## MOLYGREASE CSX 2

### Description

- Calcium complex grease (Calcium sulphonate complex) for multiple applications. Exhibits excellent mechanical stability, resistance to leaching and separation of oil.
- It has excellent adhesion to metal surfaces and withstands high pressures.

### Application

- Multiple applications greases particularly where high operating temperatures and long lasting lubrication under severe conditions in the presence of water are required in vehicles, industry and shipping. Widely used in steel mills, mines, shipyards and construction sites.

### Advantages

- Extremely high drop point.
- High ability to absorb free water, without losing thickener consistency.
- Stability and resistance to shear.
- Wide temperature range of effective operation.
- High resistance to extreme operating conditions

### Teknik Özellikler

Property	Test Method	Typical Values
NLGI Grades	-	2
Dropping Point	ASTM D 566	>300
Kinematic Viskosity @40°C, cSt	ASTM D 445	460
Cone Penetration @25°C, mm -1 (worked 60 strokes)	ASTM D 217	265-295
Flash Point, °C	ASTM D 92	>250
Working Temperature, °C	-	-20, +220
TIMKEN OK Load Test (lbs)	ASTM D 2509	>15
Copper Corrosion, Cu	ASTM D 4048	1a
Copper Strip Corrosion Test	ASTM D 130	1a

*\*The values given here are the estimated values of the product. It does not determine the product specification.*

- For information on the safe handling and use of this product, refer to its Material Safety Data Sheet.